

CAVI PVC UL-CSA

UL-CSA PVC WIRES

Cavi unipolari isolati in PVC per il mercato Nord Americano.
Single-core PVC insulated wires for the north American market.



1. Conduttore | Conductor
2. Gomma siliconica PVC | Silicone rubber PVC

Configurazioni | Configurations

		80°C 300 V		90°C 300 V	105°C 300 V	80°C 600 V				
Style Style		1039	1497	1706	1569	1007	1011	1013	1101	1498
Sezione Size										
AWG	mm ²	Spessore di isolamento Insulation thickness (mils; 1 mils = 0,0254 mm)								
30	0,05									
28	0,08									
26	0,13									
24	0,2	15-12	16/14	15/13	15/13	15/13	30/27	30/27		31/28
22	0,32	15-12	16/14	15/13	15/13	15/13	30/27	30/27		31/28
20	0,51	15-12	16/14	15/13	15/13	15/13	30/27	30/27		31/28
18	0,82	15-12	16/14	15/13	15/13	15/13	30/27	30/27		31/28
16	1,3	15-12	16/14	15/13	15/13	15/13	30/27	30/27		31/28
14	2,07				15/13		30/27	30/27	15/13	31/28
12	3,3				15/13		30/27	30/27	15/13	31/28
10	5,25				15/13		30/27	30/27	15/13	31/28
9	6,62						30/27	30/27		31/28
8	8,35						45/40	45/40		
7	10,6						45/40	45/40		
6	13,3						60/54	60/54		
5	16,8						60/54	60/54		
4	21,1						60/54	60/54		
3	26,6						60/54	60/54		
2	33,6						60/54	60/54		
1	42,3						80/72	80/72		
0	53,4						80/72	80/72		
2/0	67,5						80/72	80/72		
3/0	85						80/72	80/72		
4/0	107						80/72	80/72		
250 MCM	126						95/86	95/86		
300 MCM	152						95/86	95/86		
350 MCM	177						95/86	95/86		
400 MCM	202						95/86	95/86		
500 MCM	253						95/86	95/86		
600 MCM	304									
700 MCM	354									
750 MCM	380									

I dati e le illustrazioni non sono impegnativi e potrebbero variare a seguito di modifiche ritenute opportune dal costruttore.
Data and sketches are not binding and can be varied as a consequence of modifications deemed necessary by the manufacturer.

Norme | Standards



UL-758

Confezionamento | Packaging



Approvazioni | Approvals



90°C 600 V	105°C 600 V							105°C 1000 V
1499	1015	1028	1230	1283	1284	1647	1702	10269
Spessore di isolamento Insulation thickness (mils; 1 mils = 0,0254 mm)								
31/28	30/27		30/27			31/28	30/27	45/40
31/28	30/27	45/40	30/27			31/28	30/27	45/40
31/28	30/27	45/40	30/27			31/28	30/27	45/40
31/28	30/27	45/40	30/27			31/28	30/27	45/40
31/28	30/27	45/40	30/27			31/28	30/27	45/40
31/28	30/27	45/40	30/27			31/28	30/27	45/40
31/28	30/27	45/40	30/27			31/28	30/27	45/40
31/28	30/27	45/40	30/27			31/28	30/27	45/40
	45/40	45/40		60/54	80/72		45/40	60/54
	45/40	60/54		60/54	80/72		60/54	60/54
	60/54	60/54		60/54	80/72		60/54	60/54
	60/54			60/54	80/72		60/54	60/54
	60/54			60/54	80/72		60/54	60/54
	60/54			60/54	80/72		60/54	60/54
	80/72				80/72		80/72	80/72
	80/72				80/72		80/72	80/72
	80/72				80/72		80/72	80/72
	80/72				80/72		80/72	80/72
	80/72				80/72		80/72	80/72
	95/86				95/86			95/86
	95/86				95/86			95/86
	95/86				95/86			95/86
	95/86				95/86			95/86
	95/86				95/86			95/86

PVC

