

CAVI SILICONE UL-CSA

UL-CSA SILICONE WIRES

Cavi unipolari isolati in gomma siliconica, per il mercato Nord Americano.

Single-core silicone rubber insulated cables, for the North American market.



1. Connettore | Conductor
2. Gomma siliconica | Silicone rubber

Configurazioni | Configurations

		150°C 300 V				150°C 600 V															
Style <i>Style</i>		3099	3132	3136	3140	3113	3133	3134	3137	3138	3123	3141	3142	3212	3213	3214	3529	3530	3566	3604	
Sezione <i>Size</i>																					
AWG	mm²	Spessore di isolamento <i>Insulation thickness (mils; 1 mils = 0,0254 mm)</i>																			
30	0,05		15/13				30/27				30/27									30/27	
28	0,08		15/13				30/27				30/27									30/27	
26	0,13		15/13	45/40	60/54		30/27		45/40		30/27	60/54		45/40			30/27	30/27		30/27	
24	0,2		15/13	45/40	60/54		30/27		45/40		30/27	60/54		45/40			30/27	30/27		30/27	
22	0,32		15/13	45/40	60/54		30/27		45/40		30/27	60/54		45/40			30/27	30/27		30/27	
20	0,51	30/27	15/13	45/40	60/54		30/27		45/40		30/27	60/54		45/40			30/27	30/27	45/40	30/27	
18	0,82	30/27	15/13			60/54	30/27	30/27		45/40	30/27		60/54	45/40			30/27	30/27	45/40	30/27	
16	1,3	30/27	15/13				30/27	30/27		45/40	30/27		60/54	45/40			30/27	30/27	45/40	30/27	
14	2,07							30/27		45/40			60/54	45/40			30/27	30/27	45/40	30/27	
12	3,3								30/27	45/40			60/54	45/40			30/27	30/27	45/40	30/27	
10	5,25									45/40				45/40			45/40	45/40	45/40	30/27	
9	6,62									45/40							45/40	45/40	60/55	30/27	
8	8,35														60/54		60/54	60/54	60/55	45/40	
7	10,6														60/54		60/54	60/54	60/55	60/54	
6	13,3														60/54		60/54	60/54	60/55	60/54	
5	16,8														60/54		60/54	60/54	60/55	60/54	
4	21,1														60/54		60/54	60/54		60/54	
3	26,6														60/54		60/54	60/54		60/54	
2	33,6														60/54		60/54	60/54		60/54	
1	42,3															80/72	80/72	80/72		80/72	
0	53,4															80/72	80/72	80/72		80/72	
2/0	67,5															80/72	80/72	80/72		80/72	
3/0	85															80/72	80/72	80/72		80/72	
4/0	107															80/72	80/72	80/72		80/72	
250 MCM	126																95/85	95/85		95/85	
300 MCM	152																95/85	95/85		95/85	
350 MCM	177																95/85	95/85		95/85	
400 MCM	202																95/85	95/85		95/85	
500 MCM	253																95/85	95/85		95/85	
600 MCM	304																110/99	110/99		110/99	
700 MCM	354																110/99	110/99		110/99	
750 MCM	380																110/99	110/99		110/99	

Norme | Standards



UL-758

Confezionamento | Packaging



Approvazioni | Approvals



	200°C 300 V	200°C 600 V								150°C 1000 V		Style	150°C 600 V	200°C 600 V
	3367	3135	3139	3143	3262	3268	3322	3530	3604	3580	3664	Style	3099	3132
												Sezione		
												Size		
Spessore di isolamento Insulation thickness (mils; 1 mils = 0,0254 mm)														
							30/27		30/27		30/27	mm²	(mils; 1 mils = 0,0254 mm)	
							30/27		30/27		30/27	0,5	30/27	30/27
												0,75	30/27	30/27
	15/13	30/27	45/40		30/27		30/27	30/27	30/27	45/40	30/27	1	30/27	30/27
	15/13	30/27	45/40		30/27		30/27	30/27	30/27	45/40	30/27	1,5	30/27	30/27
	15/13	30/27	45/40		30/27		30/27	30/27	30/27	45/40	30/27	2,5	30/27	30/27
	15/13	30/27	45/40		30/27		30/27	30/27	30/27	45/40	30/27	4	30/27	30/27
	15/13	30/27	45/40	60/54		30/27	30/27	30/27	30/27	45/40	30/27	6	45/40	45/40
		30/27	45/40	60/54		30/27	30/27	30/27	30/27	45/40	30/27	10	60/54	60/54
		30/27	45/40	60/54		30/27		30/27	30/27	45/40	30/27	16	60/54	60/54
		30/27	45/40	60/54		30/27		30/27	30/27	45/40	30/27	25	60/54	60/54
							45/40	30/27	45/40	30/27		35	60/54	60/54
							45/40	30/27	45/40	30/27		50	80/72	80/76
							60/54	45/40	60/54	45/40		70	80/72	80/76
							60/54	60/54	60/54	60/54		95	80/72	80/76
							60/54	60/54	60/54	60/54		120	95/85	95/85
							60/54	60/54	60/54	60/54		150	95/85	95/85
							60/54	60/54	60/54	60/54		185	95/85	95/85
							60/54	60/54	60/54	60/54		240	95/85	95/85
							80/72	80/72	80/72	80/72				
							80/72	80/72	80/72	80/72				
							80/72	80/72	80/72	80/72				
							80/72	80/72	80/72	80/72				
							80/72	80/72	80/72	80/72				
							95/85	95/85	95/86	95/85				
							95/85	95/85	95/86	95/85				
							95/85	95/85	95/86	95/85				
							95/85	95/85	95/86	95/85				
							110/99	110/99		110/99				
							110/99	110/99		110/99				
							110/99	110/99		110/99				

